

Utomhusdel		RXTA30B2V1B					
Inomhusdel		FTXTA30B2V1BB					
Function				Heating season			
Kyla		Ja		Average (mandatory)		Ja	
Värme		Ja		Warmer (if designated)		nej	
				Colder (if designated)		Ja	
Parameter		Beteckning		Värde		Enhet	
Design Load				Seasonal efficiency			
Kyla		P _{designc}		3.00		kW	
heating / Average		P _{designh}		2.60		kW	
heating / Warmer		P _{designh}		-		kW	
heating / Colder		P _{designh}		3.80		kW	
				SEER		7.63	
				heating / Average		SCOP / A	
				heating / Warmer		SCOP / W	
				heating / Colder		SCOP / C	
				4.10		-	
Deklarerad kapacitet* för kyla, vid inomhustemperatur 27(19) °C och utomhustemperatur Tj				Deklarerad kapacitet* för kyla, vid inomhustemperatur 27(19) °C och utomhustemperatur Tj			
Tj = 35 °C		P _{dc}		3.00		kW	
Tj = 30 °C		P _{dc}		2.22		kW	
Tj = 25 °C		P _{dc}		1.56		kW	
Tj = 20 °C		P _{dc}		1.09		kW	
				Tj = 35 °C		EERd	
				Tj = 30 °C		EERd	
				Tj = 25 °C		EERd	
				Tj = 20 °C		EERd	
				4.20		-	
				5.92		-	
				8.83		-	
				12.91		-	
Declared capacity* for heating / Average season , at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance* / Average season, at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 °C		P _{dh}		2.31		kW	
Tj = 2 °C		P _{dh}		1.40		kW	
Tj = 7 °C		P _{dh}		1.04		kW	
Tj = 12 °C		P _{dh}		1.18		kW	
Tj = Bivalenttemperatur		P _{dh}		2.60		kW	
Tj = operating limit		P _{dh}		3.70		kW	
				Tj = -7 °C		COPd	
				Tj = 2 °C		COPd	
				Tj = 7 °C		COPd	
				Tj = 12 °C		COPd	
				Tj = Bivalenttemperatur		COPd	
				Tj = operating limit		COPd	
				3.62		-	
				5.18		-	
				6.19		-	
				7.59		-	
				2.85		-	
				1.73		-	
Declared capacity* for heating / Warmer season , at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance* / Warmer season, at indoor temperature 20 °C and outdoor temperature Tj			
Tj = 2 °C		P _{dh}		-		kW	
Tj = 7 °C		P _{dh}		-		kW	
Tj = 12 °C		P _{dh}		-		kW	
Tj = Bivalenttemperatur		P _{dh}		-		kW	
Tj = operating limit		P _{dh}		-		kW	
				Tj = 2 °C		COPd	
				Tj = 7 °C		COPd	
				Tj = 12 °C		COPd	
				Tj = Bivalenttemperatur		COPd	
				Tj = operating limit		COPd	
				-		-	
				-		-	
				-		-	
				-		-	
Declared capacity* for heating / Colder season , at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance* / Colder season, at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 °C		P _{dh}		2.31		kW	
Tj = 2 °C		P _{dh}		1.40		kW	
Tj = 7 °C		P _{dh}		1.04		kW	
Tj = 12 °C		P _{dh}		1.18		kW	
Tj = Bivalenttemperatur		P _{dh}		3.10		kW	
Tj = operating limit		P _{dh}		3.70		kW	
Tj = -15 °C		P _{dh}		3.10		kW	
				Tj = -7 °C		COPd	
				Tj = 2 °C		COPd	
				Tj = 7 °C		COPd	
				Tj = 12 °C		COPd	
				Tj = Bivalenttemperatur		COPd	
				Tj = operating limit		COPd	
				Tj = -15 °C		COPd	
				3.62		-	
				5.18		-	
				6.19		-	
				7.59		-	
				1.95		-	
				1.73		-	
				1.95		-	
Bivalenttemperatur				operating limit			
heating / Average		T _{biv}		-10		°C	
heating / Warmer		T _{biv}		-		°C	
heating / Colder		T _{biv}		-15		°C	
				heating / Average		T _{ol}	
				heating / Warmer		T _{ol}	
				heating / Colder		T _{ol}	
				-25		°C	
				-25		°C	
				-25		°C	
Cycling interval capacity				Cycling interval efficiency			
for cooling		P _{cycc}		-		kW	
for heating		P _{cyhc}		-		kW	
Degradation co-efficient cooling**		C _{dc}		0.25		-	
				for cooling		EER _{cycc}	
				for heating		COP _{cycc}	
				Degradation co-efficient cooling**		C _{dh}	
				0.25		-	
				-		-	
				-		-	
Electric power input in power models other than 'active mode'				Årlig elförbrukning			
Frånsläge		P _{off}		0.001		kW	
Standbyläge		P _{sb}		0.001		kW	
Termostatfrånsläge		P _{TO}		0		kW	
Vevhusvärmari läge		P _{CK}		0		kW	
				Kyla		Q _{CE}	
				heating / Average		Q _{HE}	
				heating / Warmer		Q _{HE}	
				heating / Colder		Q _{HE}	
				138		kWh/a	
				714		kWh/a	
				-		kWh/a	
				1,946		kWh/a	
Kapacitetskontroll				Övriga parametrar			
fixed		N		Sound power level (indoor/outdoor)		L _{WA}	
staged		N		Global warming potential		GWP	
variable		N		Rated air flow (indoor/outdoor)		-	
				60.0 / 61.0		db(A)	
				875		kgCO ₂ eq.	
				11.9 / 33.7		m ³ /min	
Contact details for obtaining more information				Daikin Europe N.V. Zandvoordestraat 300, B-8400 Oostende, Belgium			

* for staged capacity units, two values divided by a slash (/) will be declared in each box in the section 'Declared capacity of the unit' and 'Declared EER/COP' of the unit.

** if default C_d = 0.25 is chosen then (results from) cycling tests are not required. Otherwise either the heating or cooling cycling test value is required.